

## Ultrafast Soft Recovery Diode


### 8A 600V $t_{rr} \sim 35$ ns

#### Features

Ultrafast Recovery  
 175°C operating junction temperature  
 Designed and qualified for industrial level

#### Benefits

Reduced RFI and EMI  
 Higher frequency operation  
 Reduced snubbing  
 Reduced part count



#### Description/Applications

These diodes are optimized to reduce losses and EMI/RFI in high frequency power conditioning system. The softness of the recovery eliminates the need for a snubber in most applications. These devices are ideally suited for HF welding power converters and other applications where switching losses are not significant portion of the total losses.

#### Absolute Maximum Ratings $T_c = 25$ °C unless otherwise noted

Symbol	Parameter	Test Condition	Values	Units
$V_R$	Cathode – Anode voltage	--	600	V
$I_{F(AV)}$	Continuous forward current	$T_c = 25$ °C	8	A
$I_{FSM}$	Single pulse forward current	$T_c = 25$ °C	100	A
$I_{FRM}$	Maximum repetitive forward current	Square wave 20 kHz	16	A
$T_J, T_{STG}$	Operating and Storage Temperature Range	--	-55 to +175	°C



#### Thermal characteristics

Symbol	Parameter	Values	Units
$R_{\theta JC}$	Thermal Resistance, Junction-to-Case	0.6	°C/W

#### Electrical Characteristics $T_J = 25$ °C unless otherwise noted

Symbol	Parameter	Test Conditions	Min	Typ	Max	Units
$V_{BR}, V_R$	Breakdown Voltage, Blocking Voltage	$I_R = 100$ uA	600	--	--	V
$V_F$	Forward voltage	$I_F = 8$ A, $T_J = 25$ °C	--	1.45	1.75	V
		$I_F = 8$ A, $T_J = 125$ °C	--	1.35	1.65	V
$I_R$	Reverse Leakage Current	$V_R = V_{R rated}$	--	--	1	uA
		$V_R = V_{R rated}, T_J = 150$ °C	--	--	100	uA
$t_{rr}$	Reverse recovery time	$I_F = 0.5$ A, $I_R = 1$ A, $I_{RR} = 0.25$ A	--	--	35	ns
		$I_F = 1$ A, $V_R = 30$ V, $di/dt = -200$ A/us	--	--	35	ns

Package Information



	单位 mm		
	MIN	NOM	MAX
A	4.05	4.25	4.45
A1	1.15	1.25	1.35
A2	2.35	2.55	2.75
b	0.7	0.8	0.9
b1	1.22	1.32	1.42
c	0.4	0.45	0.5
e	2.34	2.54	2.74
E	9.95	10.15	10.35
H	15.3	15.5	15.7
H1	8.8	9	9.2
H2	13	13.5	14
H3	3.8	4	4.2
G	2.6	2.8	3
P	3.7	3.8	3.9